

A Non-Provisional Application Filing

of

Jose L. FRANCESE

and

Vincent TURTURRO

for

SUCTION ADAPTER FOR A MEDICAL INSTRUMENT

6530.0145-01

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N.W.
WASHINGTON, DC 20005
202-408-4000

BACKGROUND OF THE INVENTION

[001] This application is a continuation-in-part of U.S. Patent Application Serial No. 09/079,168, filed May 15, 1998, entitled "Biopsy Instrument Having Irrigation and Aspiration Capabilities," which was a continuation-in-part of U.S. Patent Application Serial No. 08/756,260, filed November 25, 1996, now U.S. Patent No. 5,897,507, issued April 27, 1999.

Field of the Invention

[002] This invention relates broadly to endoscopic surgical instruments. More particularly, this invention relates to an endoscopic biopsy forceps instrument with means for facilitating sample removal without withdrawal of the biopsy forceps instrument from an endoscope.

State of the Art

[003] Endoscopic biopsy procedures are typically performed with an endoscope and an endoscopic biopsy forceps device (bioptome). The endoscope is a long flexible tube carrying fiber optics and having a narrow lumen through which the bioptome is inserted. The bioptome typically includes a long flexible coil having a pair of opposed jaws at the distal end and manual actuation means at the proximal end. Manipulation of the actuation means opens and closes the jaws. During a biopsy tissue sampling operation, the surgeon guides the endoscope to the biopsy site while viewing the biopsy site through the fiber optics of the endoscope. The bioptome is inserted through the narrow lumen of the endoscope until the opposed jaws arrive at the biopsy site. While viewing the biopsy site through the fiber optics

FOR FILING

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N.W.
WASHINGTON, DC 20005
202-406-4000

of the endoscope, the surgeon positions the jaws around a tissue to be sampled and manipulates the actuation means so that the jaws close around the tissue. A sample of the tissue is then cut and/or torn away from the biopsy site while it is trapped between the jaws of the bioptome. Keeping the jaws closed, the surgeon withdraws the bioptome from the endoscope and then opens the jaws to collect the biopsy tissue sample.

[004] A biopsy tissue sampling procedure often requires the taking of several tissue samples either from the same or from different biopsy sites. Unfortunately, most bioptomes are limited to taking a single tissue sample, after which the device must be withdrawn from the endoscope and the tissue collected before the device can be used again to take a second tissue sample. Several attempts have been made to provide an instrument which will allow the taking of several tissue samples before the instrument must be withdrawn and the samples collected. Problems in providing such an instrument include the extremely small size required by the narrow lumen of the endoscope and the fact that the instrument must be flexible in order to be inserted through the lumen of the endoscope. Thus, several known multiple sample biopsy instruments are precluded from use with an endoscope because of their size and rigidity. These include the "punch and suction type" instruments disclosed in U.S. Pats. No. 3,989,033 to Halpern et al. and No. 4,522,206 to Whipple et al. Both of these devices have a hollow tube with a punch at the distal end and a vacuum source coupled to the proximal end. A tissue sample is cut with the punch and suctioned away from the biopsy site through the hollow

099101-0504
FBI/DOJ

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N. W.
WASHINGTON, DC 20005
202-408-4000

[005] Efforts have been made to provide multiple sampling ability to an instrument which must traverse the narrow lumen of an endoscope. These efforts have concentrated on providing a cylindrical storage space at the distal end of the instrument wherein several tissue samples can be accumulated before the instrument is withdrawn from the endoscope. U.S. Pat. No. 4,651,753 to Lifton, for example, discloses a rigid cylindrical member attached to the distal end of a first flexible tube. The cylindrical member has a lateral opening and a concentric cylindrical knife blade is slidably mounted within the cylindrical member. A second flexible tube, concentric to the first tube is coupled to the knife blade for moving the knife blade relative to the lateral opening in the cylindrical member. A third flexible tube having a plunger tip is mounted within the second flexible tube and a vacuum source (a syringe) is coupled to the proximal end of the third tube. A tissue sample is taken by bringing the lateral opening of the cylindrical member upon the biopsy site, applying vacuum with the syringe to draw tissue into the lateral opening, and pushing the second flexible tube forward to move the knife blade across the lateral opening. A tissue sample is thereby cut and trapped inside the cylindrical knife within the cylindrical member. The third flexible tube is then pushed forward moving its plunger end against the tissue sample and pushing it forward into a cylindrical storage space at the distal end of the cylindrical member. Approximately six

[illegible]

[007] A more convenient endoscopic multiple sample biopsy device is disclosed in U.S. Pat. No. 5,171,255 to Rydell. Rydell provides a flexible endoscopic instrument with a knife-sharp cutting cylinder at its distal end. A coaxial anvil is coupled to a pull wire and is actuated in the same manner as conventional biopsy forceps. When the anvil is drawn into the cylinder, tissue located between the anvil and the cylinder is cut and pushed into a storage space within the cylinder. Several

[008] A multiple sample biopsy forceps of a more traditional form is disclosed in co-owned U.S. Pat. No. 5,542,432 to Slater et al. Slater et al. discloses an endoscopic multiple sample biopsy forceps having a jaw assembly which includes a pair of opposed toothed jaw cups each of which is coupled by a resilient arm to a base member. The base member of the jaw assembly is mounted inside a cylinder and axial movement of one of the jaw assembly and cylinder relative to the other draws the arms of the jaws into the cylinder or moves the cylinder over the arms of the jaws to bring the jaw cups together in a biting action. The arms of the jaws effectively form a storage chamber which extends proximally from the lower jaw cup and prevents accumulated biopsy samples from being squeezed laterally out from between the jaws during repeated opening and closing of the jaws and the lower jaw cup enhances movement of the biopsy samples into the storage chamber. The device can hold up to four samples before it must be retrieved out of the endoscope. However, in some biopsy procedures it is sometimes desirable to retrieve more. In addition, it has been found that samples within the chamber can stick together and make determinations of which sample came from which biopsy site somewhat difficult.

[009] U.S. Pat. No. 5,538,008 to Crowe discloses a multiple sample bioptome which purports to take several samples and to transfer each sample by water pressure through a duct to the proximal end of the instrument, where each sample can be individually retrieved. The device includes a plastic jaw set biased in an open position and coupled to the distal end of an elongate tube, up to seven feet long. The tube defines a duct. A sleeve extends over the tube and a water flow passage is provided between the tube and the sleeve. An aperture is provided in the tube to permit the water flow passage to meet the duct at the distal end of the tube. Withdrawing the tube into the sleeve is disclosed to force the jaws closed and enable a sample to be cut from tissue and lodge in the duct. The water flow passage is disclosed to enable water to flow under pressure from the proximal end of passage to the distal end of the passage, through the aperture and into the distal end of the duct and to be aspirated to the proximal end of the duct, thereby transferring with it any sample contained in the duct to the proximal end where the sample can be retrieved.

[010] While on paper the Crowe device is appealing, in practice the design is impractical and flawed. For example, it would be very difficult, if not impossible, to slide the elongate tube, up to seven feet in length, relative to a sleeve of substantially the same length. It would also be difficult to maintain an unobstructed water flow passage between the tube and sleeve as the tube and sleeve curve and bend through the body. Furthermore, in order for the jaws to cut a tissue sample, the tube and jaws must be drawn into the sleeve, thereby undesirably pulling the jaws away from the tissue to be sampled.

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N. W.
WASHINGTON, DC 20005
202-408-4000

[012] One possible way to overcome this problem would be to connect both the endoscope and the suction endoscopic device to the suction source via a two-way valve. A two-way valve would allow flow of suction to only one device at a time. The drawbacks to using a two-way valve are the inconvenience of manually switching the two-way valve every time that suction is needed by either device or the costs associated with implementing automatic switching.

LAW OFFICES
FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N. W.
WASHINGTON, DC 20005
202-408-4000

the restriction openings and noting that the flow is directly proportional and the pressure differential is inversely proportional to the size of the restriction opening, the flow and pressure differentials could be controlled. The primary drawback to using such a restriction on the port for the endoscope is that a small opening could easily clog, since the main function for suction in the endoscope is to eliminate fluids and solids, such as waste or small resections, from the patient.

SUMMARY OF THE INVENTION

[014] It is therefore an object of the invention to provide an endoscopic biopsy forceps instrument which permits numerous tissue samples to be taken from a patient without removing the forceps from within the patient.

[015] It is another object of the invention to provide an endoscopic biopsy forceps instrument which can individually retrieve each of several tissue samples from the forceps without removing the forceps from the patient.

[016] It is a further object of the invention to provide an endoscopic biopsy forceps instrument which can take tissue samples located either distally or laterally relative to the instrument.

[017] It is an additional object of the invention to provide an endoscopic biopsy forceps instrument which irrigates the forceps and aspirates tissue samples contained therein.

[018] It is also an object of the invention to provide an endoscopic biopsy forceps instrument which includes a reservoir to catch samples aspirated through the instrument.

[019] It is an even further object of the invention to provide a suction adapter having ports for the parallel connection of an endoscope with another endoscopic

device capable of accommodating suction wherein adequate suction is supplied to both the endoscope and the other endoscopic device and switching between ports is not necessary.

[020] It is an additional object of the invention to provide a suction adapter having ports for the parallel connection of an endoscope with another endoscopic device wherein a flow restricting valve allows for the passage of relatively large pieces of debris while generally maintaining a desired pressure differential.

[021] In accord with these objects which will be discussed in detail below, an endoscopic biopsy forceps instrument is provided and generally includes a proximal actuation handle, a distal forceps assembly, a control member coupled to the proximal actuation handle and the distal forceps assembly, and a flexible multi-lumen tubular member having an irrigation conduit, an aspiration conduit, and a control conduit which receives the control member.

[022] According to a preferred embodiment of the invention, the proximal actuation handle includes a shaft and a spool slidably mounted on the shaft. The actuation handle is also provided with a proximal irrigation passage, a sample chamber, a sample catch member, and a pinch valve which regulates irrigation and aspiration. The proximal irrigation passage is coupled to the irrigation conduit and to an irrigation coupling tube. The sample chamber is coupled to the aspiration conduit and to an aspiration coupling tube. The sample catch member includes a screen which is inserted into the sample chamber and filters out tissue samples from the aspirated fluid. The irrigation coupling tube and the aspiration coupling tube extend through the pinch valve which operates to control the flow of fluid through the tubes. The actuation handle is coupled to the proximal ends of both the flexible tubular

member and the control member and moves the control member relative to the tubular member.

[023] The distal assembly is coupled to the distal end of the tubular member and includes a hollow jaw cup coupled over the distal end of the aspiration conduit and a hollow movable jaw pivotally coupled adjacent the irrigation conduit. The jaw cup is preferably formed from a hard plastic and has a blunt cutting surface, while the movable jaw is preferably a metal jaw with a sharp cutting edge. The movable jaw is further coupled to the control member, such that actuation of the actuation handle moves the movable jaw relative to the jaw cup, and thereby moves the jaws from an open position to a closed position. Moving the hollow jaws to a closed position provides a substantially fluidtight coupling between the irrigation and aspiration conduits.

[024] It will be appreciated that the distal end of the instrument is brought into contact with tissue of which a sample is required and the actuation handle is actuated to close the jaws and cut off a tissue sample. With the jaws in a closed position, water is irrigated through the irrigation conduit to the jaws at the distal end of the instrument and aspirated from the jaws to the proximal end of the instrument through the aspiration conduit, such that the sample cut by the jaws is aspirated with the water. As the water is aspirated it passes through the chamber and the sample is filtered onto the screen. The screen may easily be removed to retrieve the sample. It will be further appreciated that the entire procedure of cutting a sample and retrieving the sample may be performed without removing the endoscopic biopsy forceps instrument from its location within the body.

FOOTNOTES

[025] According to one embodiment of the biopsy forceps instrument, the tubular member is ovoid in shape and defines a control conduit, an irrigation conduit, and an aspiration conduit. The distal forceps assembly includes a movable jaw, and a substantially rigid molded collar which is provided with a proximal socket-like coupling means for coupling the tubular member thereto, a fixed jaw cup, a distal irrigation passage, and a control passage. The collar is of similar diameter to the endoscope and is designed to be coupled to the outside of the distal end of an endoscope by a silicone rubber sock. The movable jaw is pivotally mounted on the molded collar and is movable relative to jaw cup. The tubular member is coupled in the socket. A control wire extends through the control conduit and the control passage is coupled to the two holes in the movable jaw.

[026] According to a second embodiment, the biopsy forceps instrument includes a tubular member which defines an aspiration conduit having a circular cross section, an irrigation conduit having a kidney-shaped cross section, and two control conduits. The distal assembly includes a stationary jaw bonded to the distal end of the tubular member, and a movable jaw. The stationary jaw includes a hollow jaw cup, a clevis member and two proximal ramps. The jaw cup is located over the aspiration conduit, and the clevis and the proximal ramps extend from the jaw cup over the irrigation conduit. The movable jaw is coupled to the clevis and is guided along the proximal ramps. The two control conduits exit the distal end of the tubular member lateral of the proximal ramps. A central portion of a control member is coupled to the movable jaw and each end of the control member extends through the control conduits to the proximal end of the instrument.

[027] According to a third embodiment of the biopsy forceps instrument, the instrument includes a tubular member which defines an aspiration conduit having a circular cross section and an irrigation conduit having a crescent-shaped cross section. The distal assembly is substantially similar to the second embodiment. The proximal ramps abut and partially cover the irrigation conduit to define two entrances into the irrigation conduit for the control members. A distal end of each control member is coupled to the movable jaw and the control members extend through the entrances and into the irrigation conduit. The entrances are sufficiently small such that when the jaws are in a closed position and fluid is irrigated through the irrigation conduit to the distal assembly, substantially all of the fluid passes through the irrigation conduit and into the jaws; i.e. only an insubstantial amount of the fluid irrigated through the irrigation conduit exits through the entrances formed by the ramps.

[028] According to another aspect of the present invention, a suction adapter for use with first and second medical devices capable of accommodating suction is provided that generally includes at least three ports and a flexible flow valve. According to an embodiment, the suction adapter may include a manifold having at least three ports. The ports may include a suction port configured for connecting to a suction source, a first device port configured for accommodating the first medical device, and a second device port configured for accommodating the second medical device. The flexible flow valve has an opening and may be located between the first device port and both the second device port and the suction port.

[029] Additional objects and advantages of the invention will become apparent to those skilled in the art upon reference to the detailed description taken in conjunction with the provided figures.

BRIEF DESCRIPTION OF THE DRAWINGS

[030] FIG. 1 is a broken perspective view of a first embodiment of an endoscopic biopsy forceps instrument according to the invention;

[031] FIG. 2 is a broken perspective view of the proximal end of the first embodiment of the invention;

[032] FIG. 3 is a broken perspective view of the sample chamber of the first embodiment of the invention;

[033] FIG. 4 is a perspective view of the front side of the sample catch member of the first embodiment of the invention;

[034] FIG. 5 is a perspective view of the back side of the sample catch member of the first embodiment of the invention;

[035] FIG. 6 is an enlarged broken perspective view of the tubular member of the first embodiment of the invention;

[036] FIG. 7 is an enlarged broken perspective view of the distal assembly of the first embodiment of the invention with the jaws in an open position;

[037] FIG. 8 is an enlarged broken perspective view of the distal assembly of the first embodiment of the invention with the jaws in a closed position;

[038] FIG. 9 is a bottom end view of FIG. 8;

[039] FIG. 10 is a cross section across line 10--10 of FIG. 7;

[040] FIG. 11 is cross section across line 11--11 of FIG. 8;

- [041] FIG. 12 is a broken perspective view of the distal assembly of the first embodiment illustrating an alternate control member configuration;
- [042] FIG. 13 is a broken perspective view of the distal assembly of the first embodiment illustrating another alternate control member configuration;
- [043] FIG. 14 is a broken perspective view of a second embodiment of an endoscopic biopsy forceps instrument of the invention;
- [044] FIG. 15 is an enlarged broken transparent perspective view of the tubular member of the second embodiment of the invention;
- [045] FIG. 16 is an enlarged cross section across line 16--16 of FIG. 15;
- [046] FIG. 17 is an enlarged broken perspective view of the distal assembly of the second embodiment of the invention with the jaws in an open position;
- [047] FIG. 18 is a cross section across line 18--18 of FIG. 17;
- [048] FIG. 19 is an enlarged broken perspective view of the distal end of the second embodiment of the invention with the biopsy jaws in a closed position;
- [049] FIG. 20 is a cross section across line 20--20 of FIG. 19;
- [050] FIG. 21 is an enlarged broken transparent perspective view of the tubular member of the third embodiment of the invention;
- [051] FIG. 22 is an enlarged cross-section across line 22--22 of FIG. 21;
- [052] FIG. 23 is a enlarged broken perspective view of the distal end of a third embodiment of the invention with the jaws in an open position;
- [053] Fig. 24 is a transparent perspective view of a first embodiment of a suction adapter;
- [054] Fig. 25A is a cross-section of a second embodiment of a suction adapter;

[055] Fig. 25B is an enlarged cross-section of a flow restricting valve of the suction adapter of Fig. 25A;

[056] Fig. 26 is a detail of the flow restricting valve as seen from the distal end side of the suction adapter of Fig. 24;

[057] Fig. 27 is a detail of the flow restricting valve as seen from the proximal end side of the suction adapter of Fig. 24;

[058] Fig. 28 is a perspective view of the suction adapter of Fig. 24;

[059] Fig. 29A is a transparent view of an optional embodiment of a flow restricting valve, as seen from the upstream side;

[060] Fig. 29B is a non-transparent view of the flow restricting valve of Fig. 29A, also as seen from the upstream side;

[061] Fig. 29C is a perspective view of the flow restricting valve of Fig. 29A, as seen from the upstream side;

[062] Fig. 29D is a perspective view of the flow restricting valve of Fig. 29A, as seen from the downstream side;

[063] Fig. 30A is a transparent view of another optional embodiment of a flow restricting valve, as seen from the upstream side;

[064] Fig. 30B is a non-transparent view of the flow restricting valve of Fig. 30A, also as seen from the upstream side;

[065] Fig. 30C is a perspective view of the flow restricting valve of Fig. 30A, as seen from the upstream side;

[066] Fig. 30D is a perspective view of the flow restricting valve of Fig. 30A, as seen from the downstream side;

0097401061

[067] Fig. 31A is a transparent view of a further optional embodiment of a flow restricting valve, as seen from the downstream side;

[068] Fig. 31B is a perspective view of the flow restricting valve of Fig. 31A, also as seen from the downstream side;

[069] Fig. 32A is a transparent view of an additional optional embodiment of a flow restricting valve, as seen from the downstream side; and

[070] Fig. 32B is a perspective view of the flow restricting valve of Fig. 32A, also as seen from the downstream side.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[071] Turning now to FIG. 1, a multiple sample biopsy forceps instrument 10 is shown. The biopsy forceps instrument generally includes a proximal actuation handle 12, a flexible multi-lumen tubular member 14, a pull wire 20, and a distal assembly 22. Several coupling tubes are preferably provided to couple the proximal actuation handle 12 to the tubular member 14 and to irrigation and aspiration means. In particular, a control coupling tube 23, first and second irrigation coupling tubes 24, 25 and first and second aspiration coupling tubes 26, 27 are provided.

[072] The proximal actuation handle 12 includes a shaft 30 having a transverse slot 32 and a spool 34 slidably mounted on the shaft and having a transverse bar (not shown) extending through the slot 32, as is common in the art. The actuation handle 12 is provided with a sample chamber 42, a sample catch member 44, and a pinch valve 45 which regulates irrigation and aspiration. Turning to FIG. 2, the sample chamber 42 includes irrigation connectors 46, 47 which couple the first irrigation coupling tube 24 to the second irrigation coupling tube 25. The sample chamber 42 also includes first and second aspiration connectors 48, 49

which couple the first aspiration coupling tube 26 to the second aspiration coupling tube 27. Referring to FIGS. 3 through 5, the sample catch member 44 includes a handle portion 52, an engagement portion 54 which removably engages the sample catch member 44 to the sample chamber 42, and a screen 56. The screen 56 extends through the sample chamber 42 between the first and second aspiration connectors 48, 49. The screen 56 includes a front side 58 and a back side 60 and is provided with a plurality of perforations 62 which are preferably frustoconical in shape and expand from the front side 58 to the back side 60. The first irrigation coupling tube 26 and the first aspiration coupling tube 27 extend through the pinch valve 45 which operates to control the flow of fluid through the tubes 26, 27. The pinch valve is biased to clamp closed the first irrigation coupling tube 26 and the first aspiration coupling tube 27, i.e., to collapse the tubes on top of each other. Pressing downward on the pinch valve 45 with a practitioner's finger counters the bias of the pinch valve to permit fluid flow through the first irrigation coupling tube 26 and the first aspiration coupling tube 27.

[073] Turning to FIGS. 6 and 7, and in accord with the first embodiment of the invention, the tubular member 14 is preferably an ovoid multi-lumen extrusion. The tubular member includes a proximal end 66, a distal end 68, a control conduit 70, an irrigation conduit 72, and an aspiration conduit 74, each of which extends through the tubular member to the distal assembly 22. At the proximal end 66 of the tubular member, the control conduit 70 is coupled to the control coupling tube 23, the irrigation conduit 72 is coupled to the second irrigation coupling tube 25 and the aspiration conduit 74 is coupled to the second aspiration coupling tube 27.

[074] Referring to FIGS. 7 through 9, the distal assembly 22 includes a substantially rigid molded collar 80 and a hollow movable jaw 90. The collar 80 is preferably made from a unitary piece of polycarbonate, a glass-filled polycarbonate, a hard grade styrene, or other plastic, while the movable jaw 90 is preferably made from cast metal. The collar includes a central opening 81, a circumferential channel 83, a distally extending control passage 82, a distally extending hollow jaw mount 84, a distally extending hollow stationary jaw 88, and a proximal socket 86. The central opening 81 of the collar 80 is of similar diameter to the outer diameter of the endoscope and is designed to couple the collar to the outside of the distal end of an endoscope. The circumferential channel 81 receives a portion of a silicone rubber sock (not shown), which is used to secure the collar 80 to the endoscope.

[075] The stationary jaw 88 preferably includes a blunt edge or lip 92. The movable jaw 90 is pivotally mounted at a pivot 94 on the jaw mount 84 and is pivotable relative to stationary jaw 88. The movable jaw 90 is preferably provided with a sharp cutting edge 98, a stop 100 for limiting the extent to which the movable jaw pivots away from the stationary jaw 88, and two jaw holes 102, 104, for receiving a pull wire 20, as described below.

[076] Referring to FIGS. 9 through 11, the proximal socket 86 is aligned with the control passage 82, the jaw mount 84 and the stationary jaw 88, and is designed to receive the distal end 68 of the flexible tubular member 14. The distal end 68 of the tubular member is secured in the proximal socket 86, preferably using an adhesion bonding agent, such that the control passage 82 is coupled to the control conduit 70, the jaw mount 84 is coupled substantially fluidtight to the irrigation

conduit 72, and the stationary jaw 88 is coupled substantially fluidtight to the aspiration conduit 76.

[077] Turning back to FIGS. 1, 6, 7 and 10, a central portion of the pull wire 20 extends through the jaw holes 102, 104 and the ends of the pull wire 20 extend through the control passage 82, the control conduit 70, and the control coupling tube 23 to the spool 34. Referring to FIG. 12, alternatively the pull wire 20a forms a secure loop 106a through the jaw holes 102a, 104a by doubling back on itself and forming a twist 108a. Referring to FIG. 13, in yet another alternative, two pull wires 20b, 21b may be used, the distal end of each pull wire being coupled to a jaw hole 102b, 104b by a Z-bend 110b, 112b and extending through the control passage 82b.

[078] Referring to FIGS. 1, 7, and 8, it will be appreciated that movement of the spool 34 relative to the shaft 30 results in movement of the pull wire 20 relative to the tubular member 14 and consequently moves the movable jaw 90 relative to the stationary jaw 88 such that the jaws open (FIG. 7) and close (FIG. 8). Referring to FIGS. 7 through 11, when the stationary and movable jaws 88, 90 are in a closed position a substantially fluidtight passage is formed therebetween. Because the stationary jaw 88 is coupled to the aspiration conduit 74 and the movable jaw 90 is coupled over the irrigation conduit 72, a substantially fluidtight coupling of the irrigation and aspiration conduits is achieved.

[079] In use, it will be appreciated that the distal end of the endoscope to which the collar 80 is coupled is maneuvered adjacent the desired tissue for sampling and the distal assembly is brought into contact with tissue 110 (FIGS. 10 and 11). The actuation handle 12 is actuated to close the jaws 88, 90 and cut off a

0097404-101604
FOI b7 - 101604

tissue sample 112. When the jaws 88, 90 are in a closed position, the irrigation means and the aspiration means are activated and the first proximal irrigation coupling tube and the first proximal aspiration coupling tube 24, 26 are released from the clamping action of the pinch valve 45 by depressing the pinch valve. Irrigating fluid is thereby permitted to flow through the first and second proximal irrigation coupling tubes 24, 26, through the irrigation conduit 72 and the hollow jaw mount 84, and to the jaws 88, 90 at the distal end of the instrument. The fluid flows through the jaws and is aspirated back to the proximal end of the instrument such that the sample held within the jaws is aspirated with the water. Turning back to FIGS. 2 through 6, as the water is aspirated through the aspiration conduit 74 and into the sample chamber 42, the sample is filtered onto the screen 58. The frustoconical shape of the perforations 62 permits increased fluid flow through the perforate screen while preventing the tissue sample from passing through the screen. Irrigation and aspiration means are interrupted by releasing the pinch valve 45 such that the pinch valve clamps down on the first proximal irrigation and aspiration coupling tubes 24, 26 and causes the tubes to collapse on top of each other. The screen 58 may easily be removed to retrieve the sample by gripping the handle portion 52 of the sample catch member 44 and pulling the sample catch member from the sample chamber 42. The sample is recovered from the screen, and the sample catch member is reinserted into the sample chamber to continue the procedure. It will be further appreciated that the entire procedure of cutting a sample and retrieving the sample may be performed without removing the endoscopic multiple sample biopsy forceps instrument from its location within the body. Unlimited subsequent samples may be obtained in an identical manner.

[080] Turning to FIGS. 14 and 15, a second embodiment of a multiple sample biopsy forceps instrument 210 is shown. The instrument includes a proximal actuation handle 212, a flexible multi-lumen tubular member 214, a pull wire 220, and a distal assembly 222. Several coupling tubes are preferably provided to couple the proximal actuation handle 212 to the tubular member 214 and to irrigation and aspiration means. In particular, a Y-shaped control coupling tube 223, first and second irrigation coupling tubes 224, 225, and first and second aspiration coupling tubes 226, 227 are provided.

[081] The proximal actuation handle 212 is substantially similar to the first embodiment (with like parts having numbers incremented by 200). Referring to FIGS. 15, 16 and 17, the tubular member 214 is preferably a multi-lumen multi-layer extrusion, and preferably includes a first metal braid 276 beneath the outermost layer to add desired stiffness to the tubular member. If desired, a second metal braid 277 may be additionally provided around the aspiration conduit 274 to stiffen and support the aspiration conduit 274. The tubular member 214 has a proximal end 266, a distal end 268, two control conduits 270, 271, an irrigation conduit 272, and an aspiration conduit 274, each of the conduits 270, 271, 272, 274 extending through the tubular member to the distal assembly 222. The aspiration conduit 274 has a substantially circular cross section. The irrigation conduit 272 has a generally kidney-shaped cross section and is separated from the aspiration conduit 274 by a membrane 275. The control conduits 270, 271 are preferably situated one on either end of the membrane 275.

[082] Referring to FIGS. 17 through 20, the distal assembly 222 according to the second embodiment of the invention includes a stationary jaw 281 coupled,

preferably by adhesion bonding, to the distal end 268 of the tubular member. The stationary jaw 281, preferably made of plastic, includes a jaw cup 288, an integral central clevis 293 and integral proximal ramps 295, 296. The jaw cup 288 is located over the aspiration conduit 274 and preferably has a blunt cutting surface or lip 292. The central clevis 293 and proximal ramps 295, 296 extend from the stationary jaw 281 and abut and partially cover the irrigation conduit. A movable jaw 290, preferably made of metal, is provided with a sharp cutting edge 298, defines two jaw holes 302, 304 for receiving a pull wire 220, and is provided with two bosses 312, 314 for mounting the jaw. The bosses 312, 314 loosely engage the central clevis 293 and a pivot pin 294 extends through the bosses and the central clevis. The ramps 295, 296 of the stationary jaw 281 guide the movable jaw 290 when opening and closing and assist to form a substantially fluidtight passage between the movable jaw 290 and the stationary jaw cup 288 when the jaws are in a closed position. A central portion of the pull wire 220 which is perpendicular to the longitudinal axis of the instrument extends through the jaw holes 302, 304 and the ends of the pull wire extend into the control conduits 270, 271. Turning back to FIG. 15, the Y-shaped coupling tube 223 facilitates alignment of the ends of the pull wire 220 for coupling the pull wire to the proximal actuation handle. The pull wire 220 may be coated, e.g., in a plastic, to inhibit the pull wire from cutting into the tubular member.

[083] Referring to FIGS. 18 and 20, the distal end 268 of the tubular member is inserted through the lumen of an endoscope to a biopsy site. The jaws 288, 290 are moved into a closed position cutting off a tissue sample and further providing a substantially fluidtight coupling between the irrigation and aspiration

conduits 272, 274. While it appears from the illustrations of FIGS. 18 and 20 that the irrigation conduit 272 is obstructed at the distal end by clevis 293, it will be appreciated that the irrigation conduit 272 is substantially wider than the clevis and that fluid may flow around the clevis to the aspiration conduit 274.

[084] Turning now to FIGS. 21 through 23, a third embodiment of a multiple sample biopsy forceps, substantially similar to the second embodiment (with like parts having numbers incremented by another 200) is shown. The tubular member 414 has a proximal end 466, a distal end 468, an irrigation conduit 472, and an aspiration conduit 474. The aspiration conduit 474 has a substantially circular cross section, while the irrigation conduit 472 has a generally crescent-shaped cross section. A control coupling tube 423 is coupled to the second irrigation coupling tube 425. Two pull wires 420, 421 extend through the control coupling tube 423, pass through a substantially fluidtight valve (not shown) coupling the control coupling tube 423 and the second irrigation coupling tube 425, enter into the second irrigation coupling tube 425, and extend through the irrigation conduit 472 to the distal end 468 of the tubular member. An aspiration coupling tube 427 is coupled to the aspiration conduit 474.

[085] Referring to FIG. 23, the distal assembly 422 of the third embodiment of the invention includes a stationary jaw 481 bonded to the distal end 468 of the tubular member, and a movable jaw 490 coupled thereto. The stationary jaw 481 includes a jaw cup 488, an integral central clevis 493, and ramps 495, 496. The jaw cup abuts the distal end of the tubular member and is positioned over the aspiration conduit 474 and preferably has a blunt cutting surface or lip 492. The central clevis 493 and ramps 495, 496 extend from the stationary jaw 481 and abut and partially

[illegible][illegible]

	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

105101-1012600

suction or vacuum source (not shown). The first device port 612 is separated from the suction source port 610 and the second device port 614 by a flow restricting valve 618. The first device port 612 is configured to accommodate a first device capable of accommodating suction, preferably an endoscope. The second device port 614 is configured to accommodate a second such device capable of accommodating suction, preferably a suction biopsy forceps (not shown). In the general case, the manifold could include more than three ports, and more particularly, additional device ports can be included. These other device ports could either be separated from the suction source port and any other device ports by flow restricting valves or be configured for accommodating suction without an intervening flow restricting valve. In a preferred embodiment, the second device may incorporate a flow restricting valve that is normally closed such that in an idle configuration the device does not draw suction, and only draws suction when the valve is selectively opened.

[088] As shown in Figs. 25-27, the flow restricting valve 618 may be embodied as a tricuspid valve. The flow restricting valve 618 may include a flexible membrane 620 split by cuts 622 forming flaps 624 and having at least one opening 626. In a preferred embodiment, the flexible membrane 620 would be split by at least three radial cuts 622 to form three flaps 624, although a valve having more than three cuts and three flaps falls within the scope of the invention. The cuts need not be radial nor identical in, for example, size or shape. Also in a preferred embodiment, the flexible membrane 620 is conical, but other shapes are within the scope of the invention. For example, the flexible membrane could alternatively be flat, dome-shaped, or a multi-faceted prism. Further, the opening 626 could be of

any regular or irregular shape, and the opening 626 could be centrally located but need not be, and there could be more than one opening.

[089] In alternative aspects, as shown in Fig. 24 and in greater detail in Figs. 29A-29D and 30A-30D, the flow restricting valve 618 could include flaps formed, not by cuts, but by folds. In another aspect, as shown in detail in Figs. 31A and 31B, the flow restricting valve 618 could include an even number of flaps, wherein the flaps are staggered, i.e., adjacent flaps have dissimilar geometries, while every other flap is substantially identical. In a further aspect, as shown in detail in Figs. 32A and 32B, the flow restricting valve 618 could include a series of prismatically-shaped flaps. Thus, it is conceivable that the thickness of any individual flap could vary. In yet another aspect, the flow restricting valve may consist of an elastic membrane with at least one opening. The at least one opening may elastically flex to allow the establishment of the desired pressure differential between the ports. Moreover, the opening could be a hole, slit, or any other regular or irregular shaped opening. In addition, the overall shape of the flow restricting valve 618 could be a generally conical, flat, domed, multi-faceted, or other regular or irregular shape.

[090] By controlling the physical design of the valve, the appropriate balance between flow and pressure differential may be achieved. For instance, the design parameter that control the flexibility of the membrane material and the dimensions of the overall valve may be varied. Also, for instance, the design parameters that control the geometry and configuration of the individual flaps and the cross-sectional area and configuration of the openings and of the gaps, if any, between the flaps may be varied. The flow restricting valve 618 eliminates any need for providing a switch to cycle or switch between ports.

[091] Moreover, the flow restricting valve 618 is preferably self-adjusting. In other words, because of the flexible nature of the valve and the valve flaps 624, objects or debris larger than the opening 626 can pass through. Once the debris has cleared the flow restricting valve, the valve flaps 624 can return to their normal positions, as described below, and thereby re-establish the desired pressure differential between the ports.

[092] In the idle state, the flow restricting valve 618 presents a minimal gap and/or opening 626 between its elements or flaps 624. When the suction adapter 600 is connected to a source of suction, the atmospheric pressure drops in the proximal side of the flow restricting valve where the device port 614 and the suction source port 610 are located. Since the pressure on the distal end of the flow restricting valve, i.e., where the endoscopic port is located, is now higher, the flaps 624 of the flow restricting valve 618 are pushed towards the proximal end by the suction flow. This causes the gaps and/or opening 626 between the flaps 624 to increase until a constant flow rate and pressure differential is achieved. The suction or negative pressure on the proximal side is now a fraction of the maximum suction, i.e., the suction available if the flow restricting valve was plugged. Thus, by adjusting the flow rate at the flow restricting valve 618, both device ports 612, 614 can effectively share a single suction or vacuum source.

[093] Manifold 602 may be made of any suitable bio-compatible material or materials. For instance, the manifold may be made of one or more bio-compatible plastic materials. Similarly, the flow restricting valve 618 may also be made of any suitable bio-compatible material or materials, preferably a bio-compatible plastic material. In a preferred embodiment, the manifold is manufactured of plastic by

injection molding and all features are molded in one piece. However, the manifold could be formed from two or more separately manufactured pieces. For instance, the endoscope port could be attached to a simple tee-connector, which tee-connector provides the suction source port and the other device port. Further, the manifold could be manufactured separately from, or integrally with, the flow restricting valve. In a further preferred embodiment, the manifold and flow restricting valve are integrally manufactured by injection molding.

[094] There have been described and illustrated herein several embodiments of a multiple sample endoscopic biopsy instrument and several embodiments of a suction adapter. While particular embodiments of the invention have been described, it is not intended that the invention be limited thereto, as it is intended that the invention be as broad in scope as the art will allow and that the specification be read likewise.

[095] Therefore, for instance, while a particular manner of coupling the proximal actuation handle to the distal assembly has been disclosed for the several embodiments, it will be appreciated that other manners of coupling the proximal and distal assemblies may be used as well.

[096] Furthermore, while the stationary jaw is disclosed as preferably being made of plastic and the movable jaw is disclosed as being made of metal it will be appreciated both the stationary jaw and the movable jaw may be made from plastic, metal, or another material. Moreover, while the movable jaw is disclosed as preferably being made from cast metal, it will be appreciated that the movable jaw, when made of metal, may alternatively be made by machining or M.I.M.

[097] Further, while both jaws are shown without teeth, one or both of the jaws may include teeth along their mating surface. In fact, the teeth may be arranged radially as disclosed in co-owned U.S. Pat. No. 5,507,296.

[098] Also, while one or two pull wires are disclosed with respect to certain embodiments, it will be appreciated that in each embodiment either one or two pull wires may be used, in manners described herein.

[099] Furthermore, while the stationary jaw is disclosed as being coupled to the aspiration tube and the movable jaw is disclosed as being coupled to the irrigation conduit, it will be appreciated that the stationary jaw may be coupled to the irrigation conduit and the movable jaw may be coupled to the aspiration conduit. Moreover, it will be appreciated that both the jaws may be movable about the distal end of the tubular member. In addition, while particular configurations have been disclosed in reference to coupling the proximal actuation handle to the tubular member, it will be appreciated that other configurations can be used as well.

[100] It will therefore be appreciated by those skilled in the art that yet other modifications could be made to the provided invention without deviating from its spirit and scope as so claimed.

003401-001
F09T F04C2500

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N. W.
WASHINGTON, DC 20005
202-408-4000